



Elvari™ ADA Compliant Hand Dryer

Key Features

- High quality and modern style complements other <u>Elvari™ products</u>
- Dual air outlets resulting in enhanced drying efficiency and quieter operation
- Adjustable sensing distance and air speed for customized performance
- Includes a carbon filter for filtering and trapping of volatile organic compounds (VOCs), gases, and odors
- Includes a 3M filtrete with a MERV rating of 12 and filters 80%—89.9% of 1.0—3.0 micron particles and 90% or greater of 3.0—10.0 micron particles

Operation

No-touch operation. 60 second auto shutoff timing protection. Sensor range is adjustable from 4–9". Standard is 6.69". LED indicator will illuminate when unit is activated.

Guide Specification

ADA slim profile, surface-mounted hand dryer shall be constructed from 20-gauge, 300 series stainless steel in a brushed #3 satin finish or optional electrocoat finishes. Welded mounting frame for added strength. Hand dryer shall operate at 72–78 dB with an air speed of 70–82 m/s. Hand dryer shall be equipped with a carbon filter set, as well as a 3M filtrete filter set. Dryer shall have separate part numbers based on operating voltage of 110–120VAC and 220–240VAC input. Dryer shall have an adjustable motor wattage from 325–500W. Dryer shall have a dedicated circuit with a minimum of 15A and must be properly grounded. Dryer shall be equipped with motor thermal protection, and heater thermal protection.

Overall Dimensions:

8.5" H x 12.5" W x 3.9" D (217mm x 318mm x 100mm)

Finishes

Click on any color swatch to view as a larger image.



*Electrocoat Finishes, see Optional Electrocoat Finishes section on page 2.

Orders composed of products indicated as **BradEX**° will be available to ship in three days after receipt of order at the factory. There is no pricing penalty for this service from Bradley.

Verify all rough-in dimensions prior to installation.

Page 1 of 3 1/31/202.
This information is subject to change without notice.
Bradley_HandDryer_2B4-Series



Product Compliance



ADA / ICC ANSI A117.1, Citation 309.4



UL electrical components



CE electrical components (220-240V only)



G Mark (220-240V only)



UK Conformity Assessed

Listed by UL Environment to

· GreenGuard Gold



Product Specifications

Voltage:	110–120V or 220–240V	Consumption:	7.6–8.4A or 3.8–4.2A
Motor:	325-500W	RPM:	16,000–29,000
Noise level at 79":	72-78 dB	Output Air Volume:	42-60 CFM
Frequency:	60 Hz or 50/60 Hz	Airspeed:	70–82 m/s, Adjustable
Exit Air Temp at Ambient:	131°F	Ambient Temp:	77°F
Drying Time:	10–15 seconds	Mounting:	Surface-mounted, ADA compliant
Protection Level:	IP24 Splash Protection		

For information on Warranties, Maintenance and BAA/ARRA Compliance, visit our website at: bradleycorp.com/washroom-accessories-products

© 2024 Bradley P.O. Box 309, Menomonee Falls, WI 53052-0309 800 BRADLEY (800 272 3539) +1 262 251 6000

bradleycorp.com

View Latest Version





Elvari™ ADA Compliant Hand Dryer

Optional Electrocoat Finishes

Bradley offers an exclusive, proprietary electrocoat color process on the Elvari hand dryer models. Unlike powder coating, color is applied to the entire stainless steel part using a submersion process with electrically charged particles. This process results in a precise film thickness across all surfaces, allowing the grain of the stainless steel to show through.

Electrocoat provides complete coverage to the part and has environmental advantages such as no or low-VOC and HAPs (Hazardous Air Pollutants), heavy metal-free products, and minimum waste discharge. Bradley's electrocoat is durable and easy to clean as well as fingerprint, stain and corrosion resistant. A UV light stabilizer additive enhances resistance to weathering and color fade. Products are performance tested for adhesion following ASTM D3359-22 and impact resistance following ASTM D2794.

Model (Must select one)		
2B4	Elvari Hand Dryer	
Standard Selections (Must select one from each category)		
Mounting Type (select one)		
11	Surface Mounted	
Voltage Type (select one)		
0	110–120V	
49	220-240V	
Hand Dryer Finish Type (Must select one)		
ВВ	Brushed Black	
BR	Brushed Brass	
BZ	Brushed Bronze	
BN	Brushed Nickel	
BS	Brushed Stainless	
SS	Satin Stainless ¹	

¹ Models with Hand Dryer Finish Type SS are available with **BradEX®** expedited shipping.

Orders composed of products indicated as **BradEX**° will be available to ship in three days after receipt of order at the factory. There is no pricing penalty for this service from Bradley.

Verify all rough-in dimensions prior to installation.

Page 2 of 3 1/31/2024
This information is subject to change without notice.
Bradley_HandDryer_2B4-Series


View Latest Version


© 2024 Bradley
P.O. Box 309, Menomonee Falls, WI 53052-0309
800 BRADLEY (800 272 3539) +1 262 251 6000
bradleycorp.com





Dimensions (mm)





Orders composed of products indicated as **BradEX**° will be available to ship in three days after receipt of order at the factory. There is no pricing penalty for this service from Bradley.

 $\label{thm:constraints} \mbox{ Verify all rough-in dimensions prior to installation. }$

Page 3 of 3 1/31/2024
This information is subject to change without notice.
Bradley_HandDryer_2B4-Series

View Latest Version

© 2024 Bradley
P.O. Box 309, Menomonee Falls, WI 53052-0309
800 BRADLEY (800 272 3539) +1 262 251 6000
bradleycorp.com